

SASH SHUTTERS WITH NYLON GASKET



SAG



SAGP - CE



SAGP

SAGØ 80 ÷ 300 mm: manual

SAGPØ 80 ÷ 300 mm: pneumatic with cylinder

SAGPMØ 80÷300 mm: electropneumatic with electrovalve (Voltages available 110Vac - 220Vac - 24Vac - 24Vdc)

TECHNICAL DATA

GALVANIZED OR STAINLESS STEEL

NYLON GASKET

AVAILABLE ATEX VERSION

ISO CYLINDERS ON DEMAND on pneumatic and electropneumatic version

Ø mm	A	B	C	C (avec protection)	CYLINDRES	KG
Ø 80	160	250	340	375	1	2,6
Ø 100	180	290	400	425	1	3,3
Ø 120	200	330	460	487	1	3,9
Ø 140	220	370	520	547	1	4,4
Ø 150	230	390	540	577	1	4,7
Ø 160	240	410	580	607	1	5,5
Ø 180	260	450	640	667	2	6,2
Ø 200	280	490	700	727	2	7
Ø 220	300	530	760	787	2	10
Ø 240	320	570	820	847	2	10,4
Ø 250	330	590	840	877	2	10,7
Ø 260	340	610	870	907	2	11,5
Ø 280	360	650	930	967	2	12,3
Ø 300	380	690	990	1027	2	13

